

PRODUCT DESCRIPTION


A ready set of elements for suspension and powering (one pole) of a light-weight lighting fixture. The bottom fastener is equipped with an external connection for one pole of current. It also enables adjusting the angle at which the fixture is mounted. The bent rod, 50 cm long, acts as a power conductor. The top fastener serves as a mount to e.g. a wooden panel and a connection to the power supply

Fill empty fields


Product nr.	
Fixture type	
Company	
Job name	
Date	



RELATED PROFILES




GIZA-LL profile
Ref: C0758




OPK-4 Profile
Ref: C0370




JAZ Profile
Ref: B8547




SILER Profile
Ref: B9325



MICRO-ALU Profile
Ref: B1888




TAMI Profile
Ref: B5390




PDS-4-ALU Profile
Ref: B1718



PDS-ZM Profile
Ref: B7696



REGULOR Profile
Ref: B468+43




TEST-36 Profile
Ref: B6639




TEST-74 Profile
Ref: W4507




TETRA-43 Profile
Ref: W4476




TETRA-78 Profile
Ref: W4508




GIZA Profile
Ref: B5556




LIPOD Profile
Ref: B5554




DES Profile
Ref: 18030




GLADES Profile
Ref: 18036




BOX Profile
Ref: 00640



TESE Profile
Ref: 18021V1




3035-O Profile
Ref: B8441



PDS-ZMG Profile
Ref: C1418



MICRO-HG Profile
Ref: C1419



TAPO Profile
Ref: C1919