

VIAZACIA A UPEVNŔOVACIA TECHNIKA


SAMOZHÁŠAVÉ SŤAHOVACIE PÁSKY / SELF-EXTINGUISHING CABLE TIES

- **materiál:** polyamid PA 6,6
- **teplotný rozsah:** - 40°C do + 85°C, max +110°C
- **teplota pri použití:** - 10°C do + 60°C
- **absorpcia vlhkosti:** 2,7%
- **horľavosť:** UL 94 V0
- bezhalogénové

- material: polyamid PA 6,6
- working temperature: - 40°C to + 85°C, + 110°C for short time
- tightening temperature: - 10°C to + 60°C,
- humidity absorption: 2,7 %
- flammability rating: UL 94 V0
- Halogen free



HALOGEN FREE



RoHS PAHs Reach



Objednáv. kód	Rozmer (mm)	Max. zaťaženie	Max. priemer zväzku (mm)	Balenie (ks)
SP 2100 V0	100 x 2,5	80N	20,5	100
SP 4140 V0	140 x 3,6	180N	32,0	100
SP 4150 V0	150 x 3,6		36,0	100
SP 4200 V0	200 x 3,6		52,5	100
SP 5200 V0	200 x 4,8		49,5	100
SP 5290 V0	290 x 4,5	230N	78,0	100
SP 5300 V0	300 x 4,8		81,0	100
SP 5380 V0	380 x 4,8		107,0	100
SP 8365 V0	365 x 7,5		540N	100,0
SP 8380 V0	380 x 7,5	108,0		100