

# Round IP55



## ROUND IP55



Suspension  
Ceiling mounted



On request

### IT

Apparecchio decorativo per installazione a sospensione e plafone. Corpo in acciaio al carbonio calandrato e pressopiegato. Sorgente luminosa LED multichip. Verniciatura con polveri epossidiche antigraffio. Schermo di chiusura in policarbonato opale.

### ES

Luminaria decorativa de suspensión o techo. Cuerpo de acero al carbono plegado y calandrado. Fuente de iluminación LED multichip. Recubierta con polvo epoxi anti-rayado. Difusor de policarbonato opal.

### EN

Decorative suspension or ceiling mounted lighting fitting. Bent and calendered carbon steel body. Multichip LED lighting source. Anti-scratch epoxy powder paint finish. Opal polycarbonate closing reflector.

### DE

Dekoratives Hänge- und Deckenbeleuchtungsgerät. Körper aus kalandriertem und pressgeformtem Kohlenstoffstahl. Multichip LED-Leuchtmittel. Lackierung mit kratzfesten Epoxypulvern. Abdeckschirm aus Opalpolycarbonat.

### FR

Appareil décoratif en suspension ou plafond. Corps en acier au carbone plies à la presse et calandré. Source de lumière en LED multichip. Finition de peinture en poudre époxy anti-rayures. Écran de fermeture en polycarbonate opale.

### RU

Декоративный подвесной и потолочный светильник. Корпус из прессованной и каландрированной углеродистой стали. Источник света мультикристальный СИД. Покрытие устойчивым к царапинам эпоксидным порошком. Закрывающий экран выполнен из матового поликарбоната.

### ROUND IP55 ONLY FOR SUSPENSION VERSION VARIO LUMEN | VARIO KELVIN

Code	Size	Vario Lumen Out	Watt Out	K	Beam angle	Driver Type	Driver no.	Colour
YRO60VKL	01	3350   5030   6700	36   54   73	Vario	D	ON/OFF	1	○
YRO90VKL	02	6700   10050   13400	73   109   145	Vario	D	ON/OFF	1	○
YRO120VKL	03	12060   18090   24120	131   196   261	Vario	D	ON/OFF	1	○

### ROUND IP55

Code	Size	Lumen Out	Watt Out	K	Beam angle	Driver Type	Driver no.	Colour
YRO60W	01	6700	73	W	D	ON/OFF	1	○
YRO90W	02	13400	145	W	D	ON/OFF	1	○
YRO120W	03	24120	261	W	D	ON/OFF	1	○


### ROUND IP55 COLOUR SELECTION

- SB | Silver Bombalai
- BL | Bronze Lario
- RR | Rust Rame
- BF | Beige Futuna
- WI | White Irazu
- GK | Gold Karkar
- BT | Blue Telica
- BLL | Black Lava


### ROUND IP55 BEAM ANGLE | DIMENSIONS



Size	X (mm)	Z (mm)	Kg
01	∅ 600	150	10,0
02	∅ 900	150	20,5
03	∅ 1200	150	38,0



### ROUND IP55 ACCESSORIES



NOT INCLUDED

- Order code: **YKT45** | Rose ceiling for brick installation Ø 120 mm - Height (25 mm) | 4 suspension cables, lenght: 2 mt