



VIAZACIA A UPEVNŔOVACIA TECHNIKA

ŠTAHOVACIE PÁSKY S POPISOVACÍM ŠTÍTKOM / MARKABLE CABLE TIES


- **materiál:** polyamid PA 6,6
- **teplotný rozsah:** - 40°C do + 85°C, max +110°C
- **teplota pri použití:** - 10°C do + 60°C
- **absorpcia vlhkosti:** 2,7%
- **horľavosť:** UL 94 V2

- **material:** polyamid PA 6,6
- **working temperature:** - 40°C to + 85°C, + 110°C for short time
- **tightening temperature:** - 10°C to + 60°C,
- **humidity absorption:** 2,7 %
- **flammability rating:** UL 94 V2




RoHS PAHs Reach


HALOGEN FREE



Objednáv. kód	Rozmer (mm)	Max. zaťaženie	Max. priemer zväzku (mm)	Balenie (ks)
SPP 2110	110 x 2,5	80N	18,0	100
SPR 2210	210 x 2,5		50,0	100



Objednáv. kód	Rozmer (mm)	Max. zaťaženie	Max. priemer zväzku (mm)	Balenie (ks)
SPP 2100	100 x 2,5	80N	18,0	100
SPR 2200	200 x 2,5		50,0	100



Objednáv. kód	Rozmer (mm)	Max. zaťaženie	Max. priemer zväzku (mm)	Balenie (ks)
SPP 5190	190 x 4,8	230N	46,0	100
SPP 5220	220 x 4,8		54,0	100
SPP 5270	270 x 4,8		65,0	100
SPP 5300	300 x 4,8		76,0	100
SPP 5370	370 x 4,8		120,0	100