

VIAZACIA A UPEVNŔOVACIA TECHNIKA


ŠTAHOVACIE PÁSKY PRE VYŠŠIE TEPLoty/ HEAT RESISTANT CABLE TIES

- **materiál:** polyamid PA 6,6 odolný vyššej teplote
- **teplotný rozsah:** - 40°C do + 130°C, max +150°C do 500h
- **teplota pri použití:** - 10°C do + 60°C
- **absorpcia vlhkosti:** 2,7%
- **horľavosť:** UL 94 V2
- bezhalogénové

- material: polyamid PA 6,6 heat resistant
- working temperature: - 40°C to + 130°C, + 150°C up to 500hrs
- tightening temperature: - 10°C to + 60°C,
- humidity absorption: 2,7 %
- flammability rating: UL 94 V2
- Halogen free



HALOGEN FREE



RoHS PAHs Reach



Objednáv. kód	Rozmer (mm)	Max. zaťaženie	Max. priemer zväzku (mm)	Balenie (ks)
SP 2100 HT	100 x 2,5	80N	20,5	100
SP 2120 HT	120 x 2,5		30,0	100
SP 2140 HT	140 x 2,5		33,0	100
SP 2160 HT	160 x 2,5		40,0	100
SP 2200 HT	200 x 2,5		52,5	100
SP 4140 HT	140 x 3,6	180N	33,0	100
SP 4150 HT	150 x 3,6		36,0	100
SP 4200 HT	200 x 3,6		53,0	100
SP 4300 HT	300 x 3,6		76,0	100
SP 4370 HT	370 x 3,6		102,0	100
SP 5200 HT	200 x 4,8	230N	50,0	100
SP 5290 HT	290 x 4,5		78,0	100
SP 5300 HT	300 x 4,8		76,0	100
SP 5370 HT	370 x 4,8		102,0	100
SP 5380 HT	380 x 4,8		107,0	100
SP 5430 HT	430 x 4,8	540N	110,0	100
SP 8200 HT	200 x 7,6		50,0	100
SP 8300 HT	300 x 7,6		76,0	100
SP 8370 HT	370 x 7,6		102,0	100