



# UKONČOVACIE PRVKY VODIČOV

## DUTINKY PLOCHÉ S IZOLÁCIOU - PVC, double grip

- **materiál:** E-Cu, galvanicky Sn
- **izolácia:** PVC,
- **pracovná teplota :** od -10°C do +75°C
- **Cu Easy Entry Double Grip** - s Cu vložkou pre ľahké vkladanie vodiča a zosilnený spoj po zalisovaní
- UL listed, DIN 46245



- **material :** E-Cu, tin plated
- **insulation:** PVC (vinyl)
- **temperature range:** -10°C to +75°C
- **Cu Easy Entry Double Grip** - with copper sleeve
- UL listed, DIN 46245

Objednáv. kód	Prierez (mm <sup>2</sup> )	TAB (mm)	TAB (mm)	L <sub>1</sub> (mm)	L <sub>2</sub> (mm)	s (mm)	Min. balenie (ks)
RF-F305P EE	0,5 - 1,5	2,8	0,5	20,0	8,0	0,30	100
RF-F308P EE		2,8	0,8	20,0	8,0	0,30	100
RF-F405P EE		4,8	0,5	18,0	6,0	0,30	100
RF-F408P EE		4,8	0,8	18,0	6,0	0,30	100
RF-F608P EE		6,3	0,8	21,0	7,5	0,40	100
BF-F305P EE	1,5 - 2,5	2,8	0,5	20,0	8,0	0,35	100
BF-F308P EE		2,8	0,8	20,0	8,0	0,35	100
BF-F405P EE		4,8	0,5	18,0	6,0	0,35	100
BF-F408P EE		4,8	0,8	18,0	6,0	0,35	100
BF-F608P EE		6,3	0,8	21,0	7,5	0,45	100
GF-F405P EE	4,0 - 6,0	4,8	0,5	20,5	9,5	0,40	100
GF-F408P EE		4,8	0,8	20,5	9,5	0,40	100
GF-F608P EE		6,3	0,8	25,5	11,0	0,45	100