


LISOVACIE DVOJITÉ DUTINKY S PLASTOVOU IZOLÁCIOU

TWIN ENDS

- materiál dutinky: gal Sn E-Cu
- materiál izolácie: PA (nylon), PP (polypropylén)
- teplotný rozsah použitia: - 55°C do + 110°C



- material : E-Cu gal. Sn
- insulation: PA (nylon), PC (polypropylenecarbonat)
- temp. range: -55°C to +110°C
- DIN 46228 Part 4

Obj. kód code	Farba GER colour	Farba FRA colour	Farba DIN colour	L ₁	L ₂	D ₁	D ₂	S ₁	B	Balenie (ks) pack quantity
DID 0,25 - 8	Light Blue			15,0	8,0	1,15	1,8	0,15	3,4	500
DID 0,34 - 8	Blue			15,0	8,0	1,15	1,8	0,15	3,4	500
DID 0,50 - 8	Orange	White	White	14,5	8,0	1,50	2,9	0,15	5,0	500/100
DID 0,75 - 6				13,0	6,0	1,80	3,0	0,15	5,0	500/100
DID 0,75 - 8	White	Blue	Grey	14,7	8,0	1,80	3,0	0,15	5,5	500/100
DID 0,75 - 10				16,7	10,0	1,80	3,0	0,15	5,5	500/100
DID 0,75 - 12				18,0	12,0	1,80	2,7	0,15	5,4	500/100
DID 1,00 - 8				15,1	8,0	2,00	3,2	0,15	5,5	500/100
DID 1,00 - 10	Yellow	Red	Red	17,1	10,0	2,00	3,2	0,15	5,5	500/100
DID 1,00 - 12				18,0	12,0	2,10	3,5	0,15	6,5	500/100
DID 1,50 - 8	Red	Black	Black	15,5	8,0	2,30	3,4	0,15	6,4	500/100
DID 1,50 - 12				19,5	12,0	2,30	3,4	0,15	6,4	500/100
DID 2,50 - 10				18,5	10,0	2,90	4,2	0,20	8,0	250//100
DID 2,50 - 13	Blue	Grey	Blue	21,5	13,0	2,90	4,2	0,20	8,0	250/100
DID 2,50 - 18				27,0	18,0	2,90	4,5	0,20	8,0	250/100
DID 4 - 12	White	Orange	White	23,1	12,0	3,80	5,0	0,20	8,8	100
DID 4 - 18				28,0	14,0	3,50	5,2	0,20	9,0	100
DID 6 - 14	Black	Green	Yellow	26,1	14,0	4,90	6,0	0,20	9,5	100
DID 6 - 18				29,0	14,0	4,50	6,2	0,20	11,4	100
DID 10 - 14	White	Brown	Red	26,6	16,0	6,50	7,5	0,20	12,6	100
DID 16 - 14	Green	White	Blue	31,3	14,0	8,30	9,7	0,20	19,0	50
DID 16 - 16				31,3	16,0	8,30	9,7	0,20	19,0	50