



UKONČOVACIE PRVKY VODIČOV

MEDENÉ LISOVACIE HROTY STÁČANÉ Z PLECHU BEZ IZOLÁCIE

- **materiál:** E-Cu, galvanicky Sn
- **pracovná teplota :** do +125°C
- spájkovaný spoj
- DIN 46245

- **material :** E-Cu, tin plated
- **temperature range:** to +125°C
- brazed seam
- DIN 46245



Objednáv. kód	Prierez (mm ²)	D ₁ (mm)	L ₁ (mm)	L ₂ (mm)	L ₃ (mm)	B (mm)	Min. balenie (ks)
NLK 0,5	0,1 - 0,5	1,2	18,3	5,0	10,0	1,9	100
NLK 1,5	0,5 - 1,0	1,6	18,3	5,0	10,0	1,9	100
NLK 2,5	1,5 - 2,5	2,3	18,3	5,0	10,0	1,9	100
NLK 6	4,0 - 6,0	3,6	19,5	6,0	11,0	2,7	100
NLK 10	10	4,5	25,0	8,0	11,0	4,3	100
NLK 16	16	5,8	26,0	10,0	15,0	5,5	100
NLK 25	25	7,0	34,0	14,0	15,0	7,0	100
NLK 35	35	8,2	40,0	16,0	20,0	8,0	100
NLK 50	50	9,5	45,0	19,0	20,0	9,5	100
NLK 70	70	11,2	55,0	24,0	23,0	11,0	100
NLK 95	95	13,5	55,0	24,0	23,0	12,5	100