



UKONČOVACIE PRVKY VODIČOV

MEDENÉ LISOVACIE VIDLICE STÁČANÉ Z PLECHU BEZ IZOLÁCIE

- materiál: E-Cu, galvanicky Sn
- pracovná teplota : do +125°C
- spájkovaný spoj
- DIN 46245

- material : E-Cu, tin plated
- temperature range: to +125°C
- brazed seam
- DIN 46245



Objednáv. kód	Prierez (mm ²)	D ₁ (mm)	D ₃ (mm)	A (mm)	L (mm)	B (mm)	Min. balenie (ks)
NLV 0,5/2	0,1 - 0,5	1,0	2,2	4,0	8,0	5,0	100
NLV 0,5/3			3,2		8,0	5,0	100
NLV 0,5/3,5			3,7		11,0	6,0	100
NLV 0,5/4			4,3		11,0	6,5	100
NLV 0,5/5			5,3		11,0	8,0	100
NLV 1/2,5	0,5 - 1,5	1,6	2,7	5,0	10,8	6,0	100
NLV 1/3			3,2		11,0	6,0	100
NLV 1/3,5			3,7		11,0	6,0	100
NLV 1/4 S			4,3		11,0	6,4	100
NLV 1/4 N			4,3		12,0	6,8	100
NLV 1/4 B			4,3		12,0	8,0	100
NLV 1/5			5,3		13,0	10,0	100
NLV 1/6			6,5		15,0	11,0	100
NLV 1/8			8,4		17,0	12,0	100
NLV 1/10			10,5		17,0	15,0	100
NLV 2,5/3	1,5 - 2,5	2,3	3,2	5,0	13,0	5,5	100
NLV 2,5/3,5			3,7		11,0	6,0	100
NLV 2,5/4 S			4,3		16,0	6,4	100
NLV 2,5/4 N			4,3		12,0	6,8	100
NLV 2,5/4 B			4,3		11,6	8,0	100
NLV 2,5/5			5,3		14,0	10,0	100
NLV 2,5/6			6,5		16,0	11,0	100
NLV 2,5/8			8,4		16,8	14,0	100
NLV 2,5/10			10,5		18,0	15,0	100
NLV 6/4			2,5 - 6		3,6	4,3	6,0
NLV 6/5	5,3	15,0		10,0		100	
NLV 6/6	6,5	16,0		11,0		100	
NLV 6/8	8,4	19,0		14,0		100	
NLV 6/10	10,5	21,0		18,0		100	
NLV 10/5	10	4,5	5,3	8,0	16,0	10,0	100
NLV 10/6			6,5		17,0	11,0	100
NLV 16/5	16	5,8	5,3	10,0	20,0	11,0	100
NLV 16/6			6,5		20,0	11,0	100
NLV 25/5	25	7,5	5,3	11,0	25,0	12,0	100
NLV 25/6			6,5		25,0	12,0	100